The listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Previously Presented) A method of manufacturing a light-emitting device, comprising the steps of:

preparing an evaporation cell filled with an organic electroluminescence material; and

evaporating the organic electroluminescence material in an inert gas atmosphere to form a pattern of a light emitting layer comprising the organic electroluminescence material over a substrate.

2. (Previously Presented) A method of manufacturing a light-emitting device, comprising the steps of:

placing in a reaction chamber an evaporation cell containing an organic electroluminescence material and placing a shutter above an orifice of the evaporation cell;

evaporating the organic electroluminescence material in an inert gas atmosphere to form a pattern of a light emitting layer comprising the organic electroluminescence material over a substrate by opening and closing the shutter.

3. (Previously Presented) A method of manufacturing a light-emitting device, comprising the steps of:

preparing an evaporation cell filled with an organic electroluminescence material; and

evaporating the organic electroluminescence material in an inert gas atmosphere to form a light emitting layer comprising the organic electroluminescence material selectively over a pixel electrode of the light-emitting device.

4. (Previously Presented) A method of manufacturing a light-emitting device, comprising the steps of:

placing in a reaction chamber an evaporation cell containing an organic electroluminescence material and placing a shutter above an orifice of the evaporation cell;

evaporating the organic electroluminescence material in an inert gas atmosphere to form a light emitting layer comprising the organic electroluminescence material selectively over a pixel electrode of the light-emitting device by opening and closing the shutter.

- 5. (Original) A method of manufacturing a light-emitting device as claimed in claim 1, wherein more than one evaporation cell is provided.
- 6. (Original) A method of manufacturing a light-emitting device as claimed in claim 2, wherein more than one evaporation cell is provided.
- 7. (Original) A method of manufacturing a light-emitting device as claimed in claim 3, wherein more than one evaporation cell is provided.
- 8. (Original) A method of manufacturing a light-emitting device as claimed in claim 4, wherein more than one evaporation cell is provided.
- 9. (Previously Presented) A method of manufacturing a light-emitting device as claimed in claim 1, wherein the light-emitting device is a device selected from the group

of: a personal computer, a video camera, a goggle-type display, a digital camera and a cellular phone.

10. (Previously Presented) A method of manufacturing a light-emitting device as claimed in claim 2, wherein the light-emitting device is a device selected from the group of: a personal computer, a video camera, a goggle-type display, a digital camera and a

cellular phone.

11. (Previously Presented) A method of manufacturing a light-emitting device as

claimed in claim 3, wherein the light-emitting device is a device selected from the group

of: a personal computer, a video camera, a goggle-type display, a digital camera and a

cellular phone.

12. (Previously Presented) A method of manufacturing a light-emitting device as

claimed in claim 4, wherein the light-emitting device is a device selected from the group

of: a personal computer, a video camera, a goggle-type display, a digital camera and a

cellular phone.

13. (Original) A method of manufacturing a light-emitting device as claimed in

claim 1, wherein the organic electroluminescence material is a small molecule material.

14. (Original) A method of manufacturing a light-emitting device as claimed in

claim 2, wherein the organic electroluminescence material is a small molecule material.

15. (Original) A method of manufacturing a light-emitting device as claimed in

claim 3, wherein the organic electroluminescence material is a small molecule material.

- 16. (Original) A method of manufacturing a light-emitting device as claimed in claim 4, wherein the organic electroluminescence material is a small molecule material.
- 17. (Original) A method of manufacturing a light-emitting device as claimed in claim 1, wherein the organic electroluminescence material is heated in an inert gas atmosphere at an atmospheric pressure.
- 18. (Original) A method of manufacturing a light-emitting device as claimed in claim 2, wherein the organic electroluminescence material is heated in an inert gas atmosphere at an atmospheric pressure.
- 19. (Original) A method of manufacturing a light-emitting device as claimed in claim 3, wherein the organic electroluminescence material is heated in an inert gas atmosphere at an atmospheric pressure.
- 20. (Original) A method of manufacturing a light-emitting device as claimed in claim 4, wherein the organic electroluminescence material is heated in an inert gas atmosphere at an atmospheric pressure.
- 21. (Previously Presented) A method of manufacturing a light-emitting device, comprising the steps of:

preparing an evaporation cell filled with an organic electroluminescence material; evaporating the organic electroluminescence material in an inert gas atmosphere to form a light emitting layer comprising the organic electroluminescence material selectively over a pixel electrode of the light emitting device; and

moving the evaporation cell and the substrate relative to each other.

22. (Previously Presented) A method of manufacturing a light-emitting device, comprising the steps of:

placing in a reaction chamber an evaporation cell containing an organic electroluminescence material and placing a shutter above an orifice of the evaporation cell;

evaporating the organic electroluminescence material in an inert gas atmosphere to form a light emitting layer comprising the organic electroluminescence material selectively over a pixel electrode of the light-emitting device by opening and closing the shutter; and

moving the evaporation cell and the substrate relative to each other.

- 23. (Previously Presented) A method of manufacturing a light-emitting device according to claim 21, wherein the evaporation cell is moved.
- 24. (Previously Presented) A method of manufacturing a light-emitting device according to claim 22, wherein the evaporation cell is moved.
- 25. (Previously Presented) A method of manufacturing a light-emitting device according to claim 1, wherein the evaporation cell comprises a material selected from the group consisting of boron nitride, alumina and tungsten.
- 26. (Previously Presented) A method of manufacturing a light-emitting device according to claim 2, wherein the evaporation cell comprises a material selected from the group consisting of boron nitride, alumina and tungsten.
- 27. (Previously Presented) A method of manufacturing a light-emitting device according to claim 3, wherein the evaporation cell comprises a material selected from the group consisting of boron nitride, alumina and tungsten.

- 28. (Previously Presented) A method of manufacturing a light-emitting device according to claim 4, wherein the evaporation cell comprises a material selected from the group consisting of boron nitride, alumina and tungsten.
- 29. (Previously Presented) A method of manufacturing a light-emitting device according to claim 21, wherein the evaporation cell comprises a material selected from the group consisting of boron nitride, alumina and tungsten.
- 30. (Previously Presented) A method of manufacturing a light-emitting device according to claim 22, wherein the evaporation cell comprises a material selected from the group consisting of boron nitride, alumina and tungsten.
- 31. (Previously Presented) A method of manufacturing a light-emitting device according to claim 2, wherein a diameter of the orifice is several tens to several hundreds µm.
- 32. (Previously Presented) A method of manufacturing a light-emitting device according to claim 4, wherein a diameter of the orifice is several tens to several hundreds µm.
- 33. (Previously Presented) A method of manufacturing a light-emitting device according to claim 22, wherein a diameter of the orifice is several tens to several hundreds μm .
- 34. (Previously Presented) The method of manufacturing a light-emitting device according to claim 1 wherein said pattern is directly deposited from said evaporation cell.

- 35. (Previously Presented) The method of manufacturing a light-emitting device according to claim 2 wherein said pattern is directly deposited from said evaporation cell.
- 36. (Previously Presented) The method of manufacturing a light-emitting device according to claim 1 wherein said pattern is formed over said substrate without the use of a mask.
- 37. (Previously Presented) The method of manufacturing a light-emitting device according to claim 2 wherein said pattern is formed over said substrate without the use of a mask.
- 38. (Previously Presented) A method of manufacturing a light-emitting device, comprising the steps of:

preparing an evaporation cell filled with an organic electroluminescence material, said evaporation cell having an orifice like ejecting port adapted to directly deposit a pattern of a light-emitting layer comprising the organic electroluminescence material over a substrate; and

evaporating the organic electroluminescence material in an inert gas atmosphere to form the pattern of a light emitting layer comprising the organic electroluminescence material over the substrate.

39. (Previously Presented) A method of manufacturing a light-emitting device according to claim 38, wherein the evaporation cell is moved.

- 40. (Previously Presented) A method of manufacturing a light-emitting device according to claim 38, wherein the evaporation cell comprises a material selected from the group consisting of boron nitride, alumina and tungsten.
- 41. (Previously Presented) A method of manufacturing a light-emitting device according to claim 38, wherein a diameter of the orifice is several tens to several hundreds µm.
- 42. (Previously Presented) A method of manufacturing a light-emitting device according to claim 21, wherein the substrate is moved in X-Y directions.
- 43. (Previously Presented) A method of manufacturing a light-emitting device according to claim 22, wherein the substrate is moved in X-Y directions.
- 44. (New) A method of manufacturing a light-emitting device according to claim 1, wherein the pattern has a width of about 50 to 200µm.
- 45. (New) A method of manufacturing a light-emitting device according to claim 2, wherein the pattern has a width of about 50 to 200 µm.
- 46. (New) A method of manufacturing a light-emitting device according to claim 3, wherein a pattern of the light emitting layer has a width of about 50 to 200µm.
- 47. (New) A method of manufacturing a light-emitting device according to claim 4, wherein a pattern of the light emitting layer has a width of about 50 to 200μm.
- 48. (New) A method of manufacturing a light-emitting device according to claim 21, wherein a pattern of the light emitting layer has a width of about 50 to 200µm.

- 10 -
- 49. (New) A method of manufacturing a light-emitting device according to claim 22, wherein a pattern of the light emitting layer has a width of about 50 to 200µm.
- 50. (New) A method of manufacturing a light-emitting device according to claim 38, wherein the pattern has a width of about 50 to 200 µm.
- 51. (New) A method of manufacturing a light-emitting device, comprising the steps of:

preparing an evaporation cell filled with an organic material,

evaporating the organic material in an inert gas atmosphere at an atmospheric pressure;

forming a pattern comprising the organic material over a substrate; and moving the evaporation cell and the substrate relative to each other.

- 52. (New) A method of manufacturing a light-emitting device according to claim 51, wherein more than one evaporation cell is provided.
- 53. (New) A method of manufacturing a light-emitting device according to claim 51, wherein the light-emitting device is a device selected from the group of: a personal computer, a video camera, a goggle-type display, a digital camera and a cellular phone.
- 54. (New) A method of manufacturing a light-emitting device according to claim 51, wherein the evaporation cell comprises a material selected from the group consisting of boron nitride, alumina and tungsten.
- 55. (New) A method of manufacturing a light-emitting device according to claim 51, wherein the pattern has a width of about 50 to 200 µm.